



Technical Data Sheet

PRODUCT NAME:- MOC UMB PB29

PRODUCT CODE.: 7344

APPLICATION: FILM, MOLDING & COLOR COMPOUND

SL NO.	PROPERTIES	METHOD	RANGE		RESULT	
			LOWER	UPPER		
1	CARRIER RESIN	--	--	--	PE	
2	PELLET SHAPE	CYLINDRICAL/SPHERICAL	--	--	CYLINDRICAL	
3	CHEMICAL COMP.	CAS NO.	--	--	57455-37-5	
4	POLYMER	CAS NO.	--	--	9002-88-4	
5	ADDITIVE	CAS NO.	--	--	9002-88-4	
6	MFI 190°C/2.16 Kgs.	ASTM D 1238	30	40	36.10 gm/10 mint	
7	SPECIFICA GRAVITY	ASTM D 792	1.30	1.40	1.36 g/cm ³	
8	MOISTURE CONTENT 105°C	ASTM D 789	0.01	0.15	0.03%	
9	ANTIOXIDANT CONTENT	%	--	--	0.1%	
10	PIGMENT CONTENT	%	--	--	60%	
11	PELLET SIZE	VERNIER SCALE (mm)	2 mm	3 mm	2 mm	
12	PELLET COUNT	No'S/1gm	50	60	60 NoS/1gm	
13	HEAT STABILITY	ISO105A02	300°C	300°C	300°C	
14	MIGRATION	In Oil 70°C/48 hrs	1	5	5	
15	FILM MICROSCOPIC EXAMINE	In 30 micron film (Spot)	1	7	1	
16	TOXICITY	FDA	-	-	21 CFR 178.3297	
17	BULK DENSITY	ASTM S 1895/GM/CC	0.80	0.90	0.85 GM/CC	
18	LIGHT FASTNESS	ISO 105 B02	FULL TONE	TINT TONE	FULL TONE	TINT TONE
			8	8	8	8
19	WEATHER RESISTANCE	DIN 54001	FULL TONE	TINT TONE	FULL TONE	TINT TONE
			5	5	5	5

For Prayag Polytech (P) Ltd.


Technical Manager
BHAWADI