

UL312

LINEAR LOW DENSITY POLYETHYLENE

General Information

Description

- ◆ UL312 is manufactured by Unipol process technology.
- ◆ UL312 has good mechanical properties, gel free and good processability.

Additives

- ◆ Antioxidant, Slip Agent, Anti-blocking Agent

Applications

- ◆ Lamination Film

Physical Properties¹

General Properties	Test Method	Nominal Values				
Melt Flow Index	ASTM D1238	1.1	g/10min			
Density	ASTM D792	0.920	g/cm ³			
Blown Film Properties(40μm)						
Ultimate Tensile Strength	MD	ASTM D882	420	kgf/cm ²	41.2	MPa
	TD		380		37.3	
Ultimate Elongation	MD	ASTM D882	740	%		
	TD		760			
Elmendorf Tear Strength	MD	ASTM D1922	6.0	g/ μ m	240	g
	TD		11.0		440	
Dart Impact Strength	ASTM D1709	170	g			
Haze	ASTM D1003	11	%			
Gloss (45°)	ASTM D2457	73	%			

* Processing Condition : Φ 50mm LLDPE Blown Film Extruder
Temperature : 180°C, Die Gap 2.2mm, BUR 2.1, FLH 32cm

Note

ISO 9001, 14001, ITS 16949

¹ Physical Properties : these are not to be construed as specifications

www.lottechem.com