

UF914

LINEAR LOW DENSITY POLYETHYLENE

General Information

Description

- ◆ UF914 is a melt blend grade for blown film applications.
- ◆ UF914 has good optical properties and good processability.

Additives

- ◆ Antioxidant, Slip Agent, Anti-blocking Agent

Applications

- ◆ General Purpose Film

Physical Properties¹

General Properties	Test Method	Nominal Values				
Melt Flow Index	ASTM D1238	1.1	g/10min			
Density	ASTM D792	0.920	g/cm ³			
Blown Film Properties(40μm)						
Ultimate Tensile Strength	MD	ASTM D882	395	kgf/cm ²	38.7	MPa
	TD		375		36.8	
Ultimate Elongation	MD	ASTM D882	700	%		
	TD		720			
Elmendorf Tear Strength	MD	ASTM D1922	4.5	g/ μ m	180	g
	TD		9.0		360	
Dart Impact Strength	ASTM D1709	115	g			
Haze	ASTM D1003	7.5	%			
Gloss (45°)	ASTM D2457	75	%			

* Processing Condition : Φ 50mm LLDPE Blown Film Extruder
 Temperature : 180°C, Die Gap 2.2mm, BUR 2.1, FLH 32cm

Note

ISO 9001, 14001, ITS 16949

¹ Physical Properties : these are not to be construed as specifications

www.lottechem.com